

Using Interferometry to Achieve Micro-Arcsecond Astrometry

Bijan Nemati
Exoplanet Science and Technology Fair, JPL
22 February 2008







CALTECH




Searching for other 'Earths' through stellar wobble


Method 1: Measure the star's motion back and forth towards us ("Radial velocity") – Lower limits down to $\sim 20~M_{Earth}$







Method 2: Measure wobble of the star relative to the background ("Astrometry") – can do down to $\sim 1~M_{Earth}$








Why Use An Interferometer



- A 9m baseline interferometer with 30 cm apertures is equivalent to a 3 m telescope for astrometry
- In the special case of nearby exoplanet searches, an interferometer has a greater advantage.
 - The 9m baseline interferometer with 2 deg FOR is like a 30 m telescope with a 12 arcmin FOV.
- Beyond Photometry
 - Adequate sampling of the telescope PSF for the purposes of uas astrometry requires giant focal planes on the order of 1 Gpix (and mosaic focal planes may not do)
 - Systematic errors in CCD centroiding for a focal plane that is critically sampled is probably limited to $(1/2000)(\lambda/D)$ A few tens of uas may be the limit for a 1-2 m telescope, goes linearly with diameter
 - The equivalent error for an interferometer is the measuring of the white light delay. Here a precision of (1 /60,000) * λ/D has been demonstrated in the laboratory.









Stellar Astrometric Interferometer

- 1 Fringe Detector Total starlight pathlength difference
- 2 Internal Metrology Internal starlight pathlength difference
- 3 External Metrology Baseline vector








Science and Guide Interferometers








Feb. 22, 2008



Getting down to Picometers



- To detect stellar wobble due to an Earth mass planet from 10 pc away, requires ~ 1 uas precision per 'visit'
- This corresponds to ~ 44 pm in delay error (total).



- The main obstacles to getting down to this level are:
 - 1. Noise
 - Atomic & Structural Vibrations
 - Light beams average over large number of atoms on the optics surfaces
 - Vibrations along light paths are actively controlled to a few nanometers
 - Electronic Noise
 - Temporal averaging, low-noise electronic design
 - 2. Thermal Drifts
 - Affect Structure, Optics, Electronics
 - Narrow-angle: Chop between target and reference
 - Wide-angle: Use Grid observations to remove linear temporal drift each hour
 - 3. Systematic Errors
 - Field Dependent Biases: **Astrometric Grid** is used to solve for biases
 - Other Systematics: Calibration, Engineering design










Picometer Metrology Truss Testbed (Kite)



- A real example of how this works is shown below in data from SIM's external Metrology Testbed (Kite)
 - The raw gauge output shows noise at the ~30 nm level
 - The Narrow-Angle metric, however, is only a few picometers







CALTECH



SIM Micro Arcsecond Metrology Testbed (MAM)

- Create a single interferometer with a SIM-like field of regard
- Create an equally good inverse interferometer to act as a pseudo star
- Demonstrate that the white light delay and the internal delay can be measured with accuracy at the picometer level










Expectations for SIM Performance



- For planet finding, the SIM narrow-angle chop breaks down most errors into effectively random errors
- Instrumental errors in the SIM testbed (chopped) does integrate down as sqrt(T)
 - At least down to 1~2 picometer after 10⁵ sec











Backup









Exoplanet Science & Techology Fair

Von Karman




SIM PlanetQuest

National Aeronautics and

Integrationergiations, einsthemensal errors



- Instrumental errors in the SIM testbed (chopped) does integrate down as sqrt(T)
 - At least down to 1~2 picometer after 10⁵ sec



Terrestrial Planet search Single epoch precision 1µas

Terrestrial Planet search 5yr mission precision 0.14μas

Systematic error floor < 100 femtoarcsec

MAM testbed March 2006





